



BITUMEN PRIME COATING

READY TO USE BITUMEN PRIMER

DESCRIPTION

The primer presents a solution of high-quality oil bitumen with a softening temperature of no lower than 70°C in specially selected organic solvents. The primer presents a mix of high-quality bitumen and specially selected organic solvents. It has an enhanced covering capacity, penetrability and short drying time.

USES

Is intended for preparation (prime coating) of the surface before installation of torch-on or self-adhesive waterproofing material. The primer presents a mix of high-quality bitumen and specially selected organic solvents.

CONSUMPTION

- 0.25–0.35 l/m² (1 l of primer per 3.33 m²).

APPLICATION

Bitumen primer BITUMEN PRIME COATING is recommended to be applied to a processed surface by large or small paint brushes. During application the primer is brushed into the surface, it saturates and attaches itself to it, ensuring a strong adhesion of the waterproofing covering to the base

STORAGE

Store in dry place protected against sunlight at a temperature between -20°C and +30°C.
Guaranteed storage period - 18 months.

PACKING

- Bucket 10 and 20 liters.

TECHNICAL DATA

PROPERTIES	UNIT	VALUE
Drying time at 20°C	h	12
Mass fraction of non-volatile substances	%	47 - 65
Softening temperature	°C	≥ 70
Relative viscosity	s	10 - 40